

# Purolite™ IP9

聚氯乙烯, 惰性聚合物, 垫层

## 主要应用

- 水处理用垫层

## 产品优势

- 比水处理树脂更重
- 耐再生剂

## 适用系统

- 脱盐系统
- 脱碱系统
- 软化系统

## 包装样式

- 25L 阀口袋
- 1CF 纸盒
- 5 CF 纤维板桶
- 1M3 立方袋
- 42 ft³ 立方袋

## 典型物理和化学参数

聚合物骨架	聚氯乙烯
外观	浅蓝色镜片
长度	4.5 - 5.5 mm
宽度	4.5 - 5.5 mm
厚度	2.0 - 3.0 mm
比重 (最小)	1.3
包装密度 (大约)	850 - 950 g/L (53.1 - 59.4 lb/ft³)
温度限制	70 °C (158.0 °F)

Ecolab is a global developer, manufacturer, and supplier of Purolite™ Resins including ion exchange, catalyst adsorbent and advanced polymers that make the world cleaner and healthier.

[www.puoliteresins.com](http://www.puoliteresins.com)



We're ready to solve your process challenges.

For further information on products and services, visit [www.puoliteresins.com](http://www.puoliteresins.com) or complete a Contact Us form via [PuoliteResins.com/contact-us](http://PuoliteResins.com/contact-us) or use the QR code.

Contact Us Form:



The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, Purolite expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. Nothing contained herein constitutes a license to practice under any patent and it should not be construed as an inducement to infringe any patent and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement.